

## Team Reed's XT-R

### Clutch Kit, Ski-doo & Lynx 850 Turbo with Jaws Pipe.

-All models only #417224013

-Stock Belt 574 or 571

MXZ 137

-All models use 15.5g pivot bolt (35mm long),

-Run Clicker 3

-Remove 1g collar and 2g collar from stock pivot bolt

-Reinstall 2g (bigger collar) on new pivot bolt supplied in kit.

- Install 4 magnets (2.4g) in each heel-

Use my 35mm (15.5) pivot bolt supply,

#### Backcountry Model

-Stock belt 574 or 571

-heel weight 2.4g (4 magnets)

- Helix: 46/42

-Install 5g tungsten (long one) 1g (5/16" long) set screw in each ramp, all the way to the tip.

-Install 2g collar

-Secondary spring 180-303 (417127137) supplied in kit.

#### XS821 Belt

Primary Spring 150-300

Run Clicker 3

-Use 15.5g pivot bolt (35mm long),

Heel weight 2.4g (4 magnets)

2.5g tungsten (short one), 2.7g set screw.

-Secondary spring 180-303 (417127137) supplied in kit.

Straight 46 Helix

-Tune for 8000-8100 RPM. Add weight if over-revving.

- If running tune, we recommend running the XS821 Belt

With 46 Stright cut helix Available at [www.TeamReeds.com](http://www.TeamReeds.com)

850 Turbo



TR XT-R

315-323-1968

Made in USA

For tech questions or tuning advice, call 315-323-1968

THANK YOU!  
TEAM REED'S

## Team Reed's XT-R

### Clutch Kit, Ski-doo & Lynx 850 Turbo Stock Pipe.

#### STOCK BELT 571 or 574

-All models only Primary Spring 150-300 #417224013  
MXZ 137

-Stock Belt use 15.5g pivot bolt (35mm long),  
-Run Clicker 2

-Stock Belt Install 2.5 tungsten short one, 1.5 g (3/8" long) set screw in  
each ramp, all the way to the tip.

Heel weight-2.4g (4 magnets)

-

Remove 1g collar and 2g from the stock pivot bolt

Reinstall 2g (bigger collar) on new pivot bolt supplied in kit

#### (Backcountry Reinstall 1g(smallest) collar with supplied pivot bolt (35mm) in kit)

-Helix: Stock belt 48/42 -Backcountry models 46/42 –

#### XS Belt

- Use 13g pivot bolt (30mm long) supplied in kit

- Install 4 magnets (2.4g) in each heel

-Run Clicker 3

-Install 5.0g tungsten (Long one), 1 g (3/8" long) set screw  
in each ramp, all the way to the tip

-Secondary spring – All Backcountry's will get a secondary spring  
#417127137 Supplied in kit.

XS Belt straight 46

-Tune for 7800-7900 RPM. Add weight if over-revving.

- With Tune shoot for 8000 RPM

#### **Additional Information**

-Keep belt deflection tight (3/4") for best performance

#### **-Weight in kit:**

- Tungsten(silver) Short is 2.5g. Long is 5g.

- Set Screws: 1g, 1.5g, 2.0g, 2.7g

- Shoulder (belly) weight (gold) 1g ,2g, 3g, 4g

-(13.0g) 30mm Pivot bolt / (15.5g) 35mm Pivot Bolt

-Spring Cup, make sure to remove the metal cap off old spring  
cup and reinstall on new spring cup.

For tech questions or tuning advice, call 315-323-1968

THANK YOU!

TEAM REED'S