

Team Reed's 900 MAX

Clutch Kit, Ski-doo 900r Stock

2022-Current

Stock Belt (571) Instructions

XS 821 Belt See (XS 821 Belt)

- Primary spring 170-400 #417224167

-(XS 821 Belt only) Install (spider shim) .024 Shim under Governor cup

-(Stock Belt) Weight Install 4 ¼ magnets in heel/ 2.5g tungsten (Short Silver) 2.0g (1/2" long) set screw in each ramp all the way to the tip.

- Clicker (Stock Belt Clicker 2)

-(XS 821 Belt) Weight Install 3 ¼ Magnets in heel / 2.5g tungsten (short silver) 2.0g (3/8" long) set screw in each ramp all the way to the tip.

(XS821 Clicker 3)

-(Stock Belt) Install 15.5g (35mm long) Pivot Bolt with 1g collar weight

-(XS 821 Belt) Install 15.5g(35mm long) pivot bolt.

-Secondary Spring 180-303 (417127137) (comes stock)

- Helix: 48-44

-Tune for 7900-8000 RPM. Add weight if over-revving.

Team Reed's 900 MAX

Clutch Kit, Ski-doo 900r 250HP Tune

2022-Current

- Primary Spring(170-400) #417224167 with 2mm spacer under spring cup.

-Add .024 (spider shim) under governor cup

-Install 3 ¼ magnets in heel, 2.0g tungsten (1/2" long) 2g set screw screwed all the way to the tip.

-Install -13.0g Pivot bolt (30mm long)

-Secondary Spring – Stock GN/GN

- Helix: 48-44

-XS-821 Belt is a must. Available at www.teamreeds.com

-Clicker 3 tune for 8400-8600 add weight if over-revving

900r 2022-Current



TR900 MAX

315-323-1968

Made in USA

Team Reed's 900 MAX

Clutch Kit, Ski-doo 900 205-240 Tune

2022-Current

Stock Belt (571) Instructions/XS 821 Belt See (XS 821 Belt)

- Primary spring 170-400 #417224167

-(XS 821 Belt) Install (spider shim) 024 Shim under Governor cup

-(Stock Belt) Weight Install 4 ¼ magnets in heel/ 2.5g tungsten (short Silver) 2.0g set screw in each ramp all the way to the tip

- Clicker (Stock Belt Clicker 2).

-(XS 821 Belt) Weight Install 3 ¼ Magnets in heel / 2.5g tungsten (Short silver) 1.0g (5/16" long) set screw in each ramp all the way to the tip.

(XS821 Clicker 3)

-(Stock Belt) Install 15.5g Pivot Bolt with 2g shoulder weight

-(XS 821 Belt) Install 15.5g (35mm long) pivot bolt.

-Secondary Spring G/G 180-303 (417127137)

- Helix: 48-44

-Tune for 7900-8000 RPM. Add weight if over-revving.

Team Reed's 900 MAX

Clutch Kit, Ski-doo 900ACE 205 HP Tune

2022-Current

Stock Belt (551) Instructions/ XS 821 Belt See (XS 821 Belt)

- Primary spring 170-400 #417224167

- Install (spider shim) 024 Shim under Governor cup

-(Stock Belt) Weight Install 3 ¼ magnets in heel/ 2.5g tungsten (short Silver) 1.5g (3/8" long) set screw in each ramp all the way to the tip.

- Clicker (Stock Belt Clicker 3)

-(XS 821 Belt) Weight Install 3 ¼ Magnets in heel / 2.5g tungsten (Short silver) 2.0g (3/8" long) set screw in each ramp all the way to the tip.

(XS821 Clicker 3)

-(Stock Belt) Install 15.5g (35mm long) pivot Bolt

-(XS 821 Belt) Install 13g (30mm long) pivot bolt.

-Secondary Spring G/G 180-303 (417127137)

- Helix: 46-44

-Tune for 7900-8000 RPM. Add weight if over-revving.

Additional Information

-Keep belt deflection tight (3/4") for best performance

-Weight in kit: - Tungsten(silver) Short is 2.5g. Long is 5g.

- Set Screws: 1g, 1.5g, 2.0g, 2.7g

- Shoulder (belly) weight (gold) 1g, 2g, 3g, 4g

-(13.0g) 30mm Pivot bolt / (15.5g) 35mm Pivot Bolt

For tech questions or tuning advice, call 315-323-1968